

WebSensor - remote barometer with Ethernet interface

code: T2514



Atmospheric pressure t-line Web sensor. Remote alarm.

Web Sensor with built-in atmospheric pressure sensor. Display reading and pressure output is user selectable in these units: hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2.

[Easy wireless communication](#) using Web Sensor and optional [Wireless TP-LINK router](#).

Included in delivery:

- T2514 Web Sensor
- Quick start manual
- [Traceable calibration certificate](#)
- Technical support at [discussion forum](#)

Technical data

ATMOSPHERIC PRESSURE SENSOR SENSOR	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C from 800 to 1100 hPa
Resolution	0.1 hPa
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	internal atmospheric pressure sensor
Output	Ethernet
Measuring interval	2 s
Available pressure units	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	9-30 Vdc
Protection class	IP30
Dimensions	88,5 x 98 x 39,5 mm
Weight	approx. 150 g
Warranty	3 years