

# **BD-2100 moisture meter**

The best-selling BD-2100 is a versatile moisture tester. Besides testing the moisture content of your wooden floorings, it also can be used on gypsum, concrete, sheetrock and other building materials. The BD-2100 has a digital display, an adjustable alarm, and Delmhorst's exclusive calibrated drywall scale as well.



## Your Benefits:

- Bright, clear digital display
- Three scales:
  - Wood Scale 6% 40% moisture range. Use for flooring and building materials, such as wood studs, floor joists, subfloors
  - Reference Scale reads from 0 100 on a relative basis.
    Use on non-wood materials, such as concrete, plaster, and insulation
  - Gypsum Scale 0.2%-50% moisture range. Use on drywall
  - Averages up to 100 accumulated readings
- Built-in calibration check
- Audible, adjustable alarm alerts you when your pre-selected MC has been reached
- Integral contact pins mounted on top of meter provide 8mm (5/16") penetration
- Built-in connector accepts any Delmhorst electrode
- Size: 20x8x4cm (8x3x1 5/8")
- Weight: 285gr. (10 oz)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 1-year warranty

### **Special Packages:**

Moisture BD-2100 Flooring Package:

Includes meter, 26-ES electrode, extra contact pins for the meter, extra 496 pins for the 26-ES electrode, and carrying case

## Available recommended electrodes:



## 26-ES Hammer electrode

Easily check high density hardwood that short pins are unable to penetrate. It will also easily penetrate through flooring to plywood sub-floor or concrete.



## 2-E pin electrode

Great for hard to read areas. Use on timber, poles and veneer.

ArtTest B.V. Tradename Delmhorst Europe www.MoistureMetersDelmhorst.com Titaniumlaan 100 NL-5221 CK 's-Hertogenbosch The Netherlands E. info@Delmhorst.eu T. 0031 73 639 5080 F. 0031 73 631 4625 VAT NL851405848B01 EORI no. NL851405848 Cham Comm. 54695910