MOISTURE METERS



FLOORING MOISTURE METERS





info@Delmhorst.EU





WHEN ACCURACY IS THE POINT

TECHSCAN

Save time, and work with confidence, with TechScan.

The next generation of non-destructive wood moisture measurement!

REF

TECHSCAN YOUR BENEFITS

Moistrure range 5%-30%
Includes color coded reference scale

Easy to read analog display

Handheld, compact and lightweight

Temperature Range: -20 to 70°C/-4 to 158°F

Built-in calibration check

Rugged, one piece sensor measures moisture up to 8mm (3/4") deep without damaging floor

Take reading in hard-to-reach places with hold function

Adjustable alarm

Advanced RF technology quickly scans wood, drywall, concrete, and other building materials

Size: 14x8,5x3cm (5 5/8x3 5/16x1 1/4") Weight: 240gr. (8.5oz)

Rugged construction

Sturdy plastic carrying case

1-year warranty



PROSCAN

Quickly scan non-destructive wood, drywall, concrete or other building materials.

With ProScan professionals work with confidence!



PROSCAN YOUR BENEFITS

Wood Moisture Range: 5%-30% 0-100 reference scale for non-wood building materials

Handheld, compact, lightweight

Easy-to-read digital display

Quickly scan large areas

Calibrated to minimize false high readings

Built-in battery/calibration checks

Adjustable alarm

Advanced RF technology

Hold function

Built-in species corrections: range of .30-.80 SG

Rugged sensor pad: measures moisture up to 1.9cm (¾")

Size: 14x8,5x3cm (5-5/8" x 3-5/16" x 1-1/4") Weight: 241gr. (8.5 oz.)

1-year warranty



BD-10

Analog wood and non-wood moisture tester.

A great entry level meter, and is ready to go with a single button press!!



YOUR BENEFITS

Two scales:

Wood Scale 6-40%:

for flooring and building material such as wood studs, floor joists, subfloors

Reference Scale 0 - 100 use for concrete, plaster, insulation etc.

Easy-to-read analog display

Built-in calibration check

Integral contact pins mounted on meter: provide 8mm (5/16") penetration

Built-in connector: accepts any Delmhorst electrode

Size: 20x8x4cm (8x3x1 5/8") Weight: 284gr. (10 oz.)

Rugged construction: ensures years of reliable use

Sturdy plastic carrying case

1-year warranty



WHEN ACCURACY IS THE POINT.

BD-2100

Building Materials Moisture Meter for testing a variety of materials.

The best-selling BD-2100 a versatile moisture tester!

BD-2100 YOUR BENEFITS

Moisture Ranges: 6-40% on wood

0,2-50% on gypsum
0-100 relative scale for non-wood materials

Averages up to 100 accumulated readings

Built-in calibration check

Audible, adjustable alarm

Built-in calibration check

Integral contact pins mounted on the meter prove 8mm. (5/16") penetration

Built-in connector: accepts any Delmhorst electrode

Size: 20x8x4cm (8" x 3" x 1 5/8") Weight: 285gr. (10 oz.)

Rugged construction: ensures years of reliable use

Sturdy plastic carrying case

1-year warranty





TECHCHECK PLUS

Building Materials 2-in-1
Moisture Meter measures MC
by pin and scan modes.

Designed with simplicity for the most demanding job!



TECHCHECK PLUS YOUR BENEFITS

Moisture Ranges Pin Mode: 6-60% wood

0.1 - 6% drywall

Scan Mode: 0-300 reference scale

Bright, clear digital display

Integral Contact pins mounted on meter: provide 8mm (5/16") penetration

Built-in connector: accepts any Delmhorst electrode

Built-in back-light

Auto-shutoff timer

Audible, adjustable alarm

Size: 22x9x4,5cm (8 ½x3 3/8x1 ¾")

Weight: 312gr. (11 oz.)

Rugged construction

Sturdy plastic carrying case

1-year warranty





HT-4000

Fast response ultimate thermo-hygrometer for flooring installers.

Features a detachable RH sensor for testing a concrete slab!

HT-4000 Thermo-Hygrered 1000

YOUR BENEFITS

Relative Humidity Range: 0% - 100%

Temperature Range: -40°C - 124°C (-40°F - 255°F)

Dew Point Range: -40°C - 80°C (-40°F - 176°F)

GPP Range:

0.1 - 3820 GPP (Grains Per Pound)

GPK Range:

0.01 - 545 GPK (Grains Per Kilogram)

Vapor Pressure Range:

0 - 7 PSI (Pounds Per Square Inch)

Vapor Pressure Range: 0 - 47 KPA (Kilopascals)

Bright, clear digital display

Built-in back-light Auto shut-off timer

Reading HOLD Feature

Size: 22x9x4,5cm (8 ½x3 3/8 x1 ¾")

Weight: 312gr. (11 oz.)

Rugged construction

Sturdy plastic carrying case

1-year warranty



www.MoistureMetersDelmhorst.com

info@Delmhorst.EU

FLOORING MOISTURE METERS RECOMMENDED ELECTRODES AND ACCESSORIES





26-ES Wood Hammer Electrode

Will easily check high density hardwood and with the same ease it will penetrate through flooring to plywood sub-floor or concrete!

"Our products are constantly evolving to meet the needs of our customers."

We understand your needs and are there to assist you!

"If you would like to have assistance in choosing the best MC tester, send an e-mail or just call us."



2-E Wood 2Pins Electrode

Electrode great for hard to read areas. Use on timber, poles, veneer!

DELMHORST EUROPE

always a step ahead in moisture measurement!



PC/kit

Enables you to download stored readings from the TotalCheck meter to a PC via infrared linking!

WHEN
ACCURACY
IS THE
POINT



MCS-1 Wood Calibraton Block

Moisture content standards are great for verifying that your Delmhorst moisture meter is in calibration!