

# FILTER ALERTS DPG/PS Series



Combination of a differential pressure gauge and a differential pressure switch

In many situations filter monitoring requires an alarm signal and a local display. Our filter alerts are the right solution for these situations. The DPG/PS filter alerts combine differential pressure switches with gauges into one practical product offering.



## **SIMILAR PRODUCTS**

• DPI series electronic differential pressure switches

### **APPLICATIONS**

The filter alerts are a solution for systems requiring visual indication of pressure on site and a switching point signal. The filter alerts are ideal for general-purpose work in air-conditioning and ventilation, especially in monitoring of air filters for contamination.

## **MODEL SUMMARY**

Description	Model	Product code	Measurement range DPG (Pa)	Measurement range PS (Pa)
Differential pressure gauge and pressure switch combinaison	DPG600/PS600	109.002.001	0-600 Pa	40-600 Pa
Differential pressure gauge and pressure switch combinaison	DPG1,5K/PS1500	109.003.001	0–1500 Pa	100–1500 Pa

Copyright HK Instruments 2016 www.hkinstruments.fi Datasheet Version 3.0 2016

# FILTER ALERTS DPG/PS Series

### **SPECIFICATIONS**

#### **Performance**

Accuracy of gauge (FS 20 °C):

+2 %

Switching difference: DPG600/PS600: 30 Pa DPG1,5K/PS1500: 80 Pa

Accuracy of switching point (Low limit typ.):

DPG600/PS600: 40 Pa ±5 Pa DPG1,5K/PS1500: 100 Pa ±10 Pa

Accuracy of switching point (HIgh limit typ.):

DPG600/PS600: 600 Pa ±30 Pa DPG1,5K/PS1500: 1500 Pa ±50 Pa

Maximum pressure:

50 kPa Service life:

> 1 000 000 switching operations

**Technical specifications** 

Media compatibility:

Dry air or non-aggressive gases

Measuring units:

Pa

**Environment:** 

Operating temperature: -5...+60 °C Storage temperature: -40...+85 °C

**Physical** 

Case (DPG & PS):

ABS

Cover (DPG & PS):

PC

Membrane (DPG & PS):

Silicone

Machinery (DPG):

Aluminum and steel spring **Duct connectors (PS):** 

ABS

Tubing (PS):

PVC, soft

Protection standard:

IP54

**Electrical connections:** 

3-screw terminal

Cable entry:

M16

Pressure fittings:

Male Ø 5 mm

Weight:

510 g

**Conformance** 

Meets the requirements for CE marking:

EMC Directive 2014/30/EU Rohs Directive 2002/95/EY

