

MEASURING INSTRUMENTS

Export General Catalogue



ABOUT US



For more than 45 years, Sauermann Group has designed, manufactured and sold products and services dedicated to the industrial and HVACR markets. The Group specifically focuses on the detection, measurement and control of indoor air quality (IAQ).

Sauermann Group operates two main brands:

- The **Sauermann** brand, through condensate removal pumps, instruments and accessories, primarily addresses the needs of Heating, Ventilation, A/C or Refrigeration contractors.
- The **Kimo** brand, through measuring instruments, meets the air management needs in light commercial and industrial installations.

HIGH ACCURACY
UNMATCHED RELIABILITY
MULTIPLE APPLICATIONS

Measurement instruments: Sauermann measurement instruments monitor a broad spectrum of indoor air quality parameters and serve a wide range of applications, from building ventilation (heating and air conditioning) systems, to cold-chain installations and combustion gas analysis. Backed by our testing laboratories and in-house research and development programme, Sauermann instruments deliver the accuracy and reliability that HVACR engineers need.

LOW SOUND LEVEL
LOW FAIL RATE
HIGH PERFORMANCE

Condensate management solutions: Safe and effective condensate management for air quality systems can be a challenge. Sauermann pumps are designed to look good, while our patented piston technology delivers whisper-quiet operation and unrivalled reliability.



North America

● ● Sauermann N.A. Corp.,
New York City,
Yardley, PA, USA

EMEA – Europe, Middle East & Africa

● Si Invest SA,
Brussels, BELGIUM

● ● Sauermann Industrie S.A.S.,
Chevry-Cossigny,
Montpon, FRANCE

● Sauermann GmbH,
Leingarten, GERMANY

● Sauermann UK Ltd.,
Blackpool, UNITED KINGDOM

● Sauermann Iberica,
Barcelona, SPAIN

● Sauermann Italia S.r.l.,
Bologna, ITALY

Asia Pacific

● ● Sauermann China,
Shanghai (Jiading & Pudong),
CHINA

● Sauermann Australasia,
Sydney, AUSTRALIA

Content

Combustion gas
analysers

04



HVACR portable

08



Data loggers

16



Sensor
transmitters

18



Combustion gas analysers 04

- A new degree of efficiency 04
- Features 05
- Si-CA 030 / 130 / 230 06
- Mobile app 07

HVACR Portable 08

- Classes 50 / 110 / 210 / 310 . . . 08
- Multi-function 11
- Thermometers 12
- Infrared 13
- Indoor air quality monitors 14
- Air flow meter 15

Data loggers 16

- Mini / USB / Multi-function 17
- Connected 17

Sensor transmitters 18

- Monostats 20
- Class 110 / 210 R 20
- Multi-function 22
- Touch control & mobile app 24

Calibration benches 25

Temperature probes 26

- CRYO 26
- Wire probes 26
- ABS head 26
- Connection 26


Manometers 26

- Inclined 26
- Vertical 26
- Differential pressure switch 26
- Accessories 26

Our expertise 27

Combustion gas analyzers

A new degree of efficiency



Our combustion gas analyzers are ideal for maintaining combustion equipment, covering the full range of operations in residential, commercial and industrial applications.

Sauermann offers a range of compact and intuitive analysers to enhance your performance.

Sauermann's combustion gas analyzers feature the latest digital and metrology technologies, making measurements more reliable and cutting the amount of time heating engineers need to spend on-site. A user experience like no other!

Applications

- Boilers
- Water heaters
- Furnaces
- Industrial heating systems
- Burners
- Gas and diesel engines
- Industrial kilns
- Incinerators



Residential



Commercial



Industrial

Warranty



All devices come with a two-year warranty against manufacturing defects (subject to assessment by our after-sales department).

To find out more about our extended warranties and maintenance plans, please visit our website, or contact our Customer Service Department.



Features

Add a digital edge to your combustion analysis



Auto pump cut-off for high CO levels (adjustable)



Predictive maintenance with estimated sensor life & calibration reminders



Draft & differential pressure measurements



Mobile phone app for real-time remote display & control



Calculations for Combustion Efficiency, Excess Air & CO₂ %



Data management with automatic logging & report creation



Si-CA 030



Si-CA 130



Si-CA 230

	Si-CA 030	Si-CA 130	Si-CA 230
LCD display size	2.8"	4.3"	4.3"
Display resolution	320 x 240 pixels	480 x 272 pixels	480 x 272 pixels
Touch-screen display	No (5 buttons)	Yes (+ on/off button)	Yes (+ on/off button)
Dimensions (H x W x D)	9,9 x 19,4 x 4,9 cm 7.5 x 3.5 x 1.6"	9,9 x 19,4 x 4,9 cm 7.5 x 3.5 x 1.6"	11,2 x 28 x 5,5 cm 11 x 4.3 x 2"
Weight	350 g - 12 oz	350 g - 12 oz	825 g - 30 oz
No. of cells	Up to 3 (O ₂ , CO, NO)	Up to 3 (O ₂ , CO, NO, Low NO)	Up to 6 (O ₂ , CO, NO, Low NO, NO ₂ , Low NO ₂ , SO ₂ , Low SO ₂ , CxHy, H ₂ S)
Max. CO measurement	8000 ppm	8000 ppm	50 000 ppm with dilution
CO dilution	-	-	✓
Field replaceable pre-calibrated sensors	-	✓	✓
Flue gas velocity with Pitot tube	-	✓	✓
Measurement storage	Smartphone	Internal: 2000 data points + Smartphone and PC	Internal: 2000 data points + Smartphone and PC
PC software (wireless & USB)	-	✓	✓
Smartphone app (wireless)	✓	✓	✓
Combustion applications	Residential, Commercial	Residential, Commercial	Commercial, Industrial



To see our extensive range of other measurement instruments for heating applications, go to www.sauermanngroup.com

Combustion gas analyzers

A new degree of efficiency



All the essentials for combustion gas analysis

Si-CA 030

- Calculated CO₂ % value
- CO safety monitoring in ambient air
- Combustion efficiency and excess air calculations
- Emissions values adjusted for reference O₂
- NOx capable with NO sensor
- Quick and easy pump On/Off control



Color display



Auto pump cut-off for high CO levels

Comprehensive, versatile analyzer with touch-screen display

Si-CA 130

- Calculated CO₂ % value
- CO safety monitoring in ambient air
- Combustion efficiency and excess air calculations
- Emissions values adjusted for reference O₂
- NOx and low NOx capable (optional)
- One Touch Pump On/Off with Purge
- Graphical data display
- Customisable gas analysis screen



Color display



Field replaceable precalibrated sensors



State-of-the-art, industrial emissions analyzer

Si-CA 230

- Ergonomic, light weight and durable design
- One touch pump On/Off with purge
- Graphical data display
- Customisable gas analysis screen
- Emissions values adjusted for reference O₂
- CO safety monitoring in ambient air



Total NOx & Low NOx Capable




Field Replaceable Pre-Calibrated Sensors

Mobile app

Sauermann Combustion

The Sauermann Combustion app lets you control your Si-CA analyzer remotely, view measurement results in real time, and customise them before exporting in the format of your choice.

- PC software with USB and wireless connectivity
- Fast, easy wireless connection
- Remote live view of combustion analysis data as list or graph
- Remote control to change settings
- Data saving, including automatic logging
- Report creation in PDF, CSV (for Excel) and XML formats



Download Sauermann Combustion app



Accessories

Customize your own analyzer



Our combustion gas analysers are available in many different configurations, with a wide range of accessories to choose from. Contact our Customer Services team for more information about our kits and accessories, and for guidance on choosing the right options for your needs.



Smart air temperature probe with 2 m cable
Ambient CO probe
Ambient CO₂ probe



180 mm flexible probe



180 mm, 300 mm & 750 mm,
and 1 m & 1.5 m probes



Draft probe



Differential pressure kit



Smoke pump



Double tube extension, 3 m



Wireless printer



SCU for condensate removal

HVACR Portable

Instruments

Temperature / Humidity / Pressure / Air velocity / Airflow /
Air quality / Gas detection / Light / Tachometry



Class 50, 110, 210 and 310

The range of portable devices is ideal for technicians responsible for maintaining heating, ventilation, and cooling installations.

- Wireless and Smart+ probes
- Graphical wide screen
- Data recording
- Ergonomic design



Graphical display



Magnetic protective cover



IP54 housing



Interchangeable probes & modules

Datalogger

Configure / Measure / Data processing

- Configuration of instruments
- Instruments management
- Reports creation
- Customized channels
- Insert commands
- Insert legends and statistics
- Add mathematical functions



Class 50, 110 and 210



Hygrometers

HD 50 / 110
HQ 210

- 3 to 98 %RH
- -40 to +180 °C
- -50 to +80 °C_{td}
- CO: 0 to 500 ppm
- CO₂: 0 to 5000 ppm

Luxmeters

LX 50

Illuminance measurement

- 0 to 10 000 lux
- 0 to 929 fc



Tachometers

CT 50 / 110

- Optical: 60 to 60 000 rpm
- Contact: 30 to 3000 rpm



Refrigerant leak detector

Si-RD3

- Detection of all the HCFC and HFC refrigerants
- Detection of mixtures 5% hydrogen - 95% nitrogen (Nidron 5)
- Heated diode sensor
- Flexible hose



Manometers

MP 50 / 51 / 55 / 110 / 111 /
112 / 115 / 120 / 130 / 210

- Differential pressure
- ±500 Pa to ±2000 mbar
- Air velocity with Pitot tube
- 3 to 85 m/s
- Atmospheric pressure
- 800 to 1100 hPa



Anemometers

LV 50 / 110 / 111 / 117 / 130
VT 50 / 110 / 115 / 210

- Hotwire and telescopic hotwire
- 0.15 to 30 m/s
- Vane probes: Ø14, 70, 100 mm
- 0.3 to 35 m/s
- Airflow: 0 to 99 999 m³/h



The + of class 210 and 310

Designed for the field

An overmoulding made of elastomere protects the instrument, guarantees shockproofing.

Nonstop measurements

This generation of instruments has an interchangeable and rechargeable Li-ion battery.

Expandable memory (AMI 310)

Internal memory of 1000 datasets of 20 000 measuring points. Built-in location for a micro-SD memory card.

Interchangeable probes

The probes use a mini-Din connecting cable which is compatible with all probes.

Interchangeable modules

1. Climatic conditions
2. Thermocouple (4 channels)
3. Pressure
4. U Coefficient



Accessories



ABS transport case



Protective housing



Backpack



Measuring cones



Debimo blades



Adjustable wedge for telescopic vane and hotwire probes



Pitot tubes

Multi-function

Class 310

AMI 310

AMI 310 is a multi-probe instrument which can measure up to 6 parameters simultaneously.



Wireless probes



Data processing software



Interchangeable probes & modules



Micro-SD card



Graphical display



Colour wide screen



- Pressure: ± 500 Pa / ± 2500 Pa / $\pm 10\,000$ Pa
 ± 500 mbar / ± 2000 mbar
- Thermocouple: -200 to $+1760$ °C
- Pt100: -200 to $+600$ °C
- Humidity: 3 to 98 %RH
- CO: 0 to 500 ppm
- CO₂: 0 to 5000 ppm
- Air velocity: -5 to 35 m/s
- Airflow: 0 to 99 999 m³/h
- Gas detection: 0 to 10 000 ppm
- Tachometry: 30 to 60 000 rpm
- Dew-point: -50 to $+100$ °C_{td}
- Wet temperature: -50 to $+100$ °C_{tw}
- Enthalpy: 0 to 10 000 kJ/kg
- Combination ratio: 0 to 10 000 g/kg
- Calculation of U coefficient and WBGT index



Thermometers

Portable instruments

Temperature

Class 210

TM 210

The differential thermometer TM 210 allows the temperature of 4 thermocouple probes to be taken simultaneously and the differential value to be displayed.

This instrument is suitable for any process where it is necessary to control the temperature at several points.

- Temperature: -200 to +1760 °C
- 2 Pt100 channels
- 1000 datasets storage
- Calculation of U coefficient
- 4 thermocouple inputs




Wireless probes



Elastomere overmoulding



Data processing software




Interchangeable measurement modules



Thermocouple module
4 inputs



U coefficient module



SMART+ probes



TR 61/62

- 1 or 2 inputs
- Pt100
- -100 to +400 °C



TK 61/62

- 1 or 2 inputs
- Thermocouple K, J, T, S
- -200 to +1760 °C



**Hold/Min/Max
functions**



Large choice of probes



General use

- -20 to 40 °C
- Penetration probe



Infrared

KIRAY 100 / 200 / 300

- Diagnose, inspect and check any temperature, with the advantage of using "no-contact" technology
- From -50 to +1850 °C



Indoor air quality monitors

Service, Residential & Commercial Applications

IAQ analysis



CO meters

CO 50

- CO: 0 to 500 ppm
- Temperature: -20 to +80 °C
- Hold function
- 2-line display



CO 110

- CO: 0 to 500 ppm
- Temperature: -20 to +80 °C
- CO max display, two configurable alarm thresholds
- 4-line display



Thermo-hygrometer - Air quality

HQ 210

- Hygrometry, temperature, CO₂ & CO gases and air velocity measurement (depending on models)
- Up to six measurements simultaneously
- Two inputs for Pt100 temperature (-200 to +600°C)
- Large graphic display
- Interchangeable measurement modules:
1 device = several possible ranges & parameters
- Supplied with calibration certificate



Air quality

AQ 110

- CO₂: 0 to 5000 ppm
- Temperature: -20 to +80 °C
- Hold function and min-max values, selection of units
- 4-line display

Air flow meter

Air flow / Air velocity / Pressure




Air flow meter

DBM 620

Compatible with all air vent types.

- Interchangeable hoods
- Quick and easy mounting
- Simultaneous display of airflow and temperature
- Automatic airflow direction (extraction or air blast)
- From 35 to 4,250 m³/h (11 to 1181 L/s)
- Supplied with 610 x 610 mm hood and transport case



Easily edit your reports with the SmartKap application



Switch between hoods quickly and easily



Patented folding frame & space-saving hoods storage



Transport case: compact storage system



4 optional hoods are available:

- 2.36 x 2.36 ft (720 x 720 mm)
- 2.36 x 4.33 ft (720 x 1320 mm)
- 1.38 x 4.99 ft (420 x 1520 mm)
- 3.35 x 3.35 ft (1020 x 1020 mm)

Remote velocity grid

Designed for air velocity measurements on any type of large ceiling vent or diffuser.

- Average air velocity from 24 points
- Telescopic and articulated pole: maximum length 2.05 m, 0 to 90°, positioning strut
- Backpack

PROCESS CONTROL

Data loggers

Kistock

Temperature / Humidity / Pressure / Air quality / Light /
Current / Voltage / Pulse / Water pressure



Multi Application



2 programmable alarm thresholds



Up to 2,000,000 measuring points



Kilog software (option)



Anti-theft system

With the range of Kistock stand-alone data loggers and Kilog software, you can collect and analyse all the metrics of industrial climate control engineering processes, monitor the climatic environment of a chamber and respond to the traceability requirements of agri-food and pharmaceutical industries during transport.



ACCESSORIES

Probes



KNT 320



Kilog and Kilog-Lite



Anti-theft kit



Key benefits



Mobile application

- Wireless pairing
- Data visualisation
- Free download

Measuring element



Calibration data



Smart plug technology

Smart and interchangeable probes (class 320)

- Advanced technology
- Integrated calibration data



Mini

KH 50 / KT 50

Temperature, humidity

- -40 to +70 °C
- 5 to 95 %RH
- USB connection
- KH 50: IP20
- KT 50: IP65



USB

KH 120 / KT 120

Temperature, humidity

- -40 to +70 °C
- 5 to 95 %RH
- Integrated software
- USB connector



KT 50 / KT 120
EN 12830



Multi-function

KH 220 / KT 220 / KTT 220

Temperature, humidity, water pressure, light, current, voltage, pulse

- -200 to +1760 °C
- 5 to 95 %RH
- 0 to 10 000 lux
- 0 to 20 bar
- 0 to 20 mA, 0 to 600 A
- 0 to 10 V



Interchangeable probes



Connected

KT 320 / KTT 320 / KCC 320
KPA 320 / KP 320-321

Temperature, humidity, pressure, atmospheric pressure, air quality, current, voltage, pulse



Mobile application

- -200 to +1,760 °C
- 5 to 95 %RH
- 0 to 5000 ppm
- 800 to 1100 hPa
- -10 000 to +10 000 Pa
- 0 to 20 mA, 0 to 600 A
- 0 to 10 V



Wireless pairing

Transmitters


Regulation and monitoring of HVAC

Pressure / Temperature / Humidity / Air velocity and air flow / Air quality /
Solar / Light / Atmospheric pressure



Designed and manufactured in France, Sauermann and Kimo's range of transmitters can be used in all industries, in the service sector or in OEM.

From the simplest to the most elaborate, these advanced measuring instruments can be adapted to any type of application thanks to their configuration and calculation possibilities.



Configurable outputs




Visual and audible alarm



Tightness ABS housing

Overview

Transmitter sensors



Monostats & classes 110/210

Transmitter sensors

Pressure

PST / CP 110 / CP 116 / CP 210-R

- ± 100 Pa to $\pm 10\,000$ Pa
- 3 to 85 m/s
- 800 to 1100 hPa (CP 116)
- -100 to +400 °C (CP 210-R)



Humidity

HST / TH 110 / HM 110 / TH 210-R

- 0 to 100 %HR
- -40 to +180 °C

Air velocity

CTV 110 / CTV 210-R

- 0 to 30 m/s
- 0 to 99 999 m³/h
- 0 to +50 °C



Simplified calibration

Electronic board and measuring element connected to the front side of the sensor, which allows to configure and calibrate your device without causing any damage.



Temperature

TST / TM 50 / TM 110 / TM 210-R

- -100 to +400 °C
- IP65 protection



CO / CO₂ transmitters

Kimo designed CO / CO₂ transmitters in order to meet with requirements of new standards and decrees on air quality.

CO

CO 110 / COST-S

- 0 to 500 ppm

CO₂

CO 112 / COT 212-R / CO2ST-S

- 0 to 5000 ppm
- 0 to +50 °C



Solar radiation / Light

CR 110 / LR 110

- 0 to 1500 W/m²
- 0 to 10 000 Lux



LCC-S software


Configuration software for monostats, class 110, 210 and 310 transmitters

- Compatible with the whole range
- Configure your devices
- Save data
- View your measurements in real time
- Protection
- Adjustable alarm thresholds
- Save a configuration to apply it to other devices



Multi-function

High-precision transmitters



Multi-function transmitter

Si-C320

Graphical touch screen

Display and measure 4 parameters simultaneously

IP66 housing, VHP resistant

4 RCR relays (option)


4 analogue outputs

Wireless communication with mobile application (option)

- -10 000 to +10 000 Pa
- 0 to 100 %HR
- -80 to +150 °C
- 0 to 30 m/s
- 0 to 99 999 m³/h
- 800 to 1100 hPa
- CO: 0 to 500 ppm
- CO₂: 0 to 10 000 ppm
- COVT: 0 to 1000 ppb
- CO₂eq: 400 to 2000 ppm
- 800 to 1100 hPa



**Multifunction
for VAC and IAQ
applications**




**4 analogue
outputs**



**RS-485 interface
for Modbus RTU
protocol**



**4 visual and
audible alarms**



24 V_{DC} / 24 V_{AC} power supply

Other calculated parameters

- Absolute humidity, dew point, specific humidity, humidity temperature, enthalpy and freezing point.



Interchangeable probes

Si-C320 and Si-CPE320

Temperature / Humidity / Air velocity / CO / CO₂ / Pressure



1 INPUT
for probe

Flush-mount multi-function transmitter

Si-CPE320

Special for clean room
Front calibration
Simultaneous display of 1 to 3 parameters
ABS IP66 housing, vaporized hydrogen peroxide resistant
3 configurable analogue outputs
MODBUS Output

- Measuring range:
from -250 to +250 Pa



3 visual and audible alarms



Brushed 316L stainless steel front panel



Touch screen

Flush-mount display

Si-ATE320

Special for clean room
Simultaneous display of 1 to 3 parameters
ABS IP66 housing, vaporized hydrogen peroxide resistant
MODBUS Output



Large display transmitter



1 INPUT
for probe

Multi-function transmitter

CA 310

1 SPI-2 or MVA card input
3 RCR relays
Digital output (option)
Supplied with adjusting certificate

- From -10 000 to +10 000 Pa
- From 0 to 100 %HR
- From -50 to +180 °C
- From 3 to 85 m/s
- From 0 to 99 999 m³/h
- CO : from 0 to 500 ppm
- CO₂ : from 0 to 5000 ppm
- From 800 to 1100 hPa
- From 0 to 10 V
- De 0 à 20 mA



Probes for CA 310

Temperature / Humidity / Air velocity /
CO / CO₂ / Pressure...

NEW TECHNOLOGIES

Touch control and mobile application

Full Si-C320 and Si-CPE3220 setup



Trend indicator: up to 4 parameters displayed simultaneously



History: chart display



Touch screen

No physical buttons: better sealing and less mechanical failure



Simultaneous display of up to 4 measurements

Chart form display




Full device setup



Indicator lights

blue light:
wireless connection

green light:
power on



Sauermann Control app

It is also possible to control and configure the class 320 transmitters with a computer, a smartphone or a tablet via the Sauermann Control application, which allows the user to manage all the device's parameters via its wireless connection module (USB wired for computers). This app can also easily update the firmware of the instrument and its probes.

- Wireless connection with iOS and Android
- Full device control
- Downloading recorded measurements
- One-click firmware update
- Remote measurement viewing

Calibration benches

Pressure / Humidity / Temperature



Pressure generator

GP 500

The pressure generator allows to adjust and calibrate measurement instruments in laboratory or on-site.

- -2 500 to +2 500 Pa
- -10 000 to +10 000 Pa



Hygrometry bench

GH 500

Calibration of several instruments simultaneously. Multi-probe ventilated measuring chamber.

- 10 to 85 %HR



Laboratory or
on-site calibration



High accuracy



Automated or
scheduled calibration

Salt solutions

KSH11 / KSH44 / KSH85

Humidity source to test class 110, 210 and 310 portable instruments and transmitters.



Temperature

Probes

Thermocouple / Pt100
Head / Cable / ABS probes



CRYO and
Wire probes




ABS head



Connection head



Measuring range
-200 to +1150 °C



Calibration
-200 to +1500 °C



Pt100
probes



Thermocouple
probes

Liquid column manometers

Differential pressure



Inclined

- 0-5 to 0-80 mmH₂O
- Units: Pa, daPa...



Vertical

- 0-100 mmH₂O to 0-2.6 bar
- Units: mbar, Pa...



Differential pressure switch
Si-DPMS

- Setting ranges in Pa:
20-200, 50-500, 200-1000, 500-2500,
1000-5000

ACCESSORIES

To fit any installation with
proper connections



- Liquid for manometer
- Tubes, junctions
- Pressure connections, wall-crossing
connection...

Our expertise

Manufacturing / Laboratories / R&D



Customer service portal

For all requests concerning repair, returns or calibration, connect to our Customer Service Portal.



Accessible
24h/7



Quick and
simple



Real-time
tracking

[Sauermann.site/Help](https://www.sauermann.com/site/Help)

State-of-the-art facilities and highly skilled staff

The Sauermann Group relies on cutting edge expertise, with more than 20 experts working in 1500 m² of testing and calibration laboratories around the world, with production lines in France, the United States and China. Our re-

search and development is conducted in-house by a young team of 20 engineers and 10 forward-thinking technicians. Their quest for innovation and patents is focused on ergonomics, digitalisation and connected devices, along with the constant improvement of the electronic and mechanical quality of our measuring instruments and condensate pumps.

Our in-house laboratories offer testing, adjustment and calibration services for a wide range of measuring instruments.

They are also one of the pillars of our high quality after-sales service. Our after-sales service covers multiple state-of-the-art activities to address all parameters related to indoor air quality.



Calibration
and adjustment



Repair /
maintenance




Hotline



Since more than 45 years, Sauermann has been developing its expertise in metrological services in many fields:

- Temperature
- Hygrometry
- Air flow rate
- Air velocity
- Pressure
- Gas analysis
- Weighing
- Radiometry
- Tachymetry
- Luxmetry
- Electricity

Professional solutions for condensate management and indoor air quality measurement



INsights


Case studies, useful information and practical advice for HVACR and indoor air quality professionals.

sauermanngroup.com/en-US/insights

Sauermann on YouTube

Head to our YouTube channel for tutorials, webinars and product guides.

youtube.com/sauermanngroup



Scan me to view all our Sauermann and Kimo catalogues online



To learn more, please visit:
sauermanngroup.com